

SPECIFICATIONS

General specifications

MODEL	XS750-2D
Dtmenston.	
Overall length	2.160 mm (85.0 m)
Overall width	965 mm (38.0 in)
Overall height	1.185 mm (46.7 in)
Wheelbase	1.470 mm (57.9 in)
Minimum road clearance	145 mm (5.7 in)
Weight	
Net	232 kg (511 lb)
Performance	
Minimum turning radius	2,500 mm (98.4 in)
Climbing capacity	26'
Engine	
Type	4 stroke. gasoline. air-cooled. DOHC
Engine model	IJ7
Cylinder	3-cylinder in-line. Forward inclined
Displacement	747 cc (45.58 cu.in)
Bore x stroke	68 x 68.6 mm (2.677 x 2.701 i n)
Compression ratio	8.5 : 1
starting system	Electric and kick starter

MODEL	XS750-2D
<p>Ignition system</p> <p>Gasoline tank capacity</p> <p>Engine/Transmission oil quantity</p> <p>Lubricating system</p> <p>Battery type/capacity</p> <p>Generator</p> <p>Spark plug</p> <p>Carburetor -</p> <p>Air cleaner</p> <p>Clutch type</p>	<p>Battery Ignition</p> <p>17 lit (4.5 US.gal)</p> <p>Total amount: 3.5 lit (3.7 US.qt)</p> <p>Periodic oil change: 2.8 lit (3.0 US.qt)</p> <p>Wet sump</p> <p>YB14L/12V, 14AH</p> <p>A.C. generator</p> <p>N-7Y (CHAMPION) or BP-7ES (NGK)</p> <p>BS34 (SU type) x 3</p> <p>Dry foam rubber</p> <p>Wet. multiple-disc</p>
<p>Transmission.</p> <p>Primary reduction system</p> <p>Primary reduction ratio</p> <p>Secondary reduction system</p> <p>Secondary reduction ratio</p> <p>Gear box type</p> <p>Operation system</p> <p>Gear ratio. First</p> <p> Second</p> <p> Third</p> <p> Fourth</p> <p> Fifth</p>	<p>HY-VO chain</p> <p>45/27 (1.666)</p> <p>Shaft drive</p> <p>34/32, 32/1 1. 19/18 (3.262)</p> <p>Constant mesh. 5-speed forward</p> <p>Left foot operation</p> <p>32/13 (2.462)</p> <p>27/17 (1.588)</p> <p>26/20 (1.300)</p> <p>23/21 (1.0951)</p> <p>22/23 (0.956)</p>

MODEL	XS750-2D
Chassis: Frame type steering: Caster Trail Tire size/inflation Front (normal riding) Rear Braking system: Front Rear Suspension: Front Rear Shock absorber: Front Rear	Tublar. double-cradle 27 ° 114 mm (4.49 in) 3.25H- 19-4PR/1.8 kg/cm' (26 psi) 4.00H - 18 -4PR/2.0 kg/cm' (28 psi) Disc brake/Right hand operation Disc brake/Right foot operation Telescopic fork Swing arm Coil spring. oil damper Coil spring. oil damper
Electrical: Headlight Tail/brake light Flasher light Pilot lights: Flasher High beam Neutral Headlight outage Oil pressure Meter lights	12v. 50W/40W 12v. 8W (8 CP)/27W (32 CP) x 2 12v. 27W (32 CPI x 4 12v. 3.4w x 2 12v. 3.4W 12v. 3.4W 12v. 3.4W 12v. 3.4W 12v. 3.4WX4